


# WAFER HOLDER — SINGLE OW WITH OPTICAL BACKSIDE WINDOW

PRODUCT INFORMATION SHEET



Schematic diagram of the Single OW wafer holder



The Single OW wafer holder series has been used for more than 15 years in MEMS industry and research. Wafer holders are available for wafers with 3", 4", 5", 6", and 8" diameters. The Single series wafer holder protects the wafer's back side and the edge from the etchant solution.

A unique feature of the OW series is an optical backside window for inspection of the membrane thickness. Silicon membranes of about 22 µm or less are optically transmissive and appear in different shades of brown depending on their thickness. The OW series of wafer holders features a transparent back side for optical inspection without built-in illumination. Pyrex glass is used for KOH- and TMAH-etching, or as an option, a solid sapphire window for HF. The holder is made entirely from PEEK; it is suitable for nearly all etchants (KOH, TMAH, HF, H3PO4, etc.)

The wafer is sealed by a double precision O-ring system that reduces mechanical stress on the wafer to a minimum. The cover-ring on the front side holds the wafers in place, fixed by six screws. Since the customer-specific wafer thickness is manufactured as a recess into the cover-ring, all screws can be tightened using a regular wrench, regardless of the applied torque. This ensures a minimum mechanical stress on the fragile wafer.

Upon ordering the holder, the wafer thickness machined as a recess into the cover-ring needs to be specified. The holder tolerates wafers with a thickness of +/- 80 µm around the specified target thickness. If more flexibility is required, additionally cover-rings with different recesses can always be ordered.

Furthermore, the volume between the wafer and holder body is connected by a venting tube to the ambient atmosphere in order to avoid pressure caused by temperature changes.

In order to keep maintenance costs low, all O-rings have dimensions in accordance with the American AS-568 standards.

## TECHNICAL SPECIFICATIONS

Product code	Single4 OW	Single6 OW	Single8 OW
Wafer size	4" or 100 mm	6" or 150 mm	8" or 200 mm
Internal dimensions			
Width of the O-ring seal	1.78 mm	1.78 mm	2.62 mm
Recommended edge exclusion width	7 mm	10 mm	5.5 mm
Diameter of usable area	86 mm	130 mm	182 mm
Diameter of optical window	86 mm	130 mm	182 mm
External dimensions			
Diameter	140 mm	183 mm	240 mm
Thickness	18 mm (+9 mm)	18 mm (+10 mm)	20 mm (+11 mm)
Etchant compatibility	KOH, TMAH, HF and various acids	KOH, TMAH, HF and various acids	KOH, TMAH, HF and various acids
Temperature range	5° C - 150° C	5° C - 150° C	5° C - 150° C

## NOTE

AMMT manufactures wafer holders for all sizes of wafers. Holders for single chips and rectangular substrates are available as well. Please inquire for specifications and prices.

**AMMT**

AMMT GmbH — Advanced Micromachining Tools  
Anselm-Feuerbach-Strasse 6, 67227 Frankenthal, Germany  
Tel.: +49-6233-4960014, Fax:+49-6233-436214  
E-Mail: info@ammt.com, http://www.ammt.com

We want to ensure that we have close contact with our customers. If you have any questions or special requirements, please do not hesitate to get in touch with us. This product information sheet is for general information purposes only. The product descriptions and the content of this document are not a substitute for our instructions in the product manual.

Specifications contained in these pages are subject to ongoing change due to progress in research and development. AMMT reserves the right to update or modify any information without notice. This also applies to improvements and/or modifications to the products described herein. AMMT is not subject to any obligations with respect to products or services. AMMT's product information sheets do not contain any representations or warranties. All technical specifications and price information are subject to change without notice.

Copyrights 1997 - 2016 AMMT GmbH. All Rights reserved.